



Pressostati TG600
Pressure switches TG600 series

250.xx301

PRESSOSTATI DI MINIMA
LOW-LIMIT PRESSURE SWITCHES

Dati Tecnici
Technical Data

Valori di taratura in fabbrica
Factory calibration values 0,3+1,5 bar

Taratura (bar) Calibration (bar)	Precisione (bar) Precision (bar)	ΔP (bar)
0,3+0,7	±0,1	0,2 ±0,1
0,8+1,5	±0,15	0,25 ±0,1

Apertura contatto C/NO con diminuzione di pressione C/N) contact opens with decreasing pressure		
Pressione max. Max pressure	set point + 2bar	
Grado di protezione Degree of protection	IP00	
Portata contatti Contact rating	16 (4)A 250V~ - 6 (1)A 400V~	
Durata meccanica Mechanical endurance	100.000 cicli 100.000 cycles	
Temperatura ambiente max Ambient temperature max	T120	
Temperatura fluido max Fluid temperature max	T120	
Attacco Connection	ottone (ch14) R1/4 UNI ISO 7/1 brass (key14) R1/4 UNI ISO 7/1	
Involucro Enclosure	PBT	
Omologhe Approvals	ENEC 03 - CE	



Opzioni
Options


Attacchi: R1/8 (ch14) - G1/4 (ch17)
Connections: R1/8 (ch14) - G1/4 (ch17)

Altri attacchi speciali su richiesta
Other special connections on request

Contatti dorati
Golden contacts

Temperatura fluido max = T140
Fluid temperature max = T140

Schemi di collegamento
Electrical wiring



Disegno & Dimensioni
Drawing & Dimensions

