
Intellitouch CH193WiFi

Weekly programmable thermostat, ultraflat and touch screen, power supply at 230V-50Hz, with WiFi connection for remote control

Electronic programmable thermostat, white backlight LCD touch screen, and weekly program to control the heating and air-conditioning systems, with WiFi connection for remote control through APP Intelliclima+ for Smartphone and Tablet.





	Temperature regulation range	Prescribed differential*	Displayed temperature range	Adjustable antifreeze temperature range	Power supply	Contacts rating
CH193WIFI	2 ÷ 40 °C	0,3 K	-50 ÷ 50°C	2 ÷ 7°C	230V 50Hz	5(3)A 250Vca
CH193BWIFI	2 ÷ 40 °C	0,3 K	-50 ÷ 50°C	2 ÷ 7°C	230V 50Hz	5(3)A 250Vca

^{*} Differential values are referred to a thermal gradient of $4\mbox{K/h}.$

CH193WIFI black frame CH193BWIFI white frame





ELECTRIC FEATURES

Power supply: 230V-50Hz;

Wireless connection: Wi-Fi 2,4 GHz; Electrical insulation: double insulation

Pollution degree: 2; Pulse voltage: 4000V;

Connection: 3 screw terminals (contact switching NC and NO);

Type of action: 1BU (micro disconnection);

ON / OFF boiler control (settable from the main menu).

HOMOLOGATION AND STANDARDS

Complies with EN 60730-1 standards; ErP Class IV; 2% (Reg. EU 811/2013 - 813/2013); Responding to Directive 2014/53 / EU (RED).




INSTALLATION

Flush-mounting installation in 3-module 503 embedded boxes at a height of approximately 1.5 m above the floor.

OPERATION

Intellitouch programmable thermostat is provided with 6 keys and their functions change according to the displayed description correspondent to each key.



OPERATION MODES

Intellitouch programmable thermostat allows different modes of use, called programs:

MAN Manual program
AUTO Weekly program
HOLIDAY Daily program
JOLLY Temporary program

OFF Switched off system or antifreeze program

MAN

The programmable thermostat regulates the room temperature using the set temperature within 24 hours.

T1: The temperature set manually from 2 to 40°C.



AUTO 24 h

The programmable thermostat regulates the prescribed temperatures according to the schedules on weekly profile.

It has 1 winter program and 1 summer program (prescribed).

In automatic mode can be set three temperature levels T1-T2-T3:


T1 can be set from 2 to 40 $^{\circ}$ C.

T2 can be set from 2 to 40 °C.

T3 can be set from 2 to 40 °C.

Antifreeze temperature -Ta it is set from 2 to 7 °C.

Note: T3 cannot be less than T2 and T2 cannot be less than T1.




HOLIDAY

The programmable thermostat follows time and temperature settings of the day "H".

This mode stops when it is selected another operating mode. The programmable thermostat has a predefined mode - Holiday, equal to Saturday and Sunday.

In Holiday mode can be set three temperature levels T1-T2-T3.




JOLLY

The programmable thermostat controls the installation using a set temperature over a period of time ranging from 1 hour to 240 hours. At the end of the set time, the programmable thermostat returns to the previously used operation mode.

This function can be excluded at any time by setting a different operation mode.

Example: Automatic Mode - Jolly for 1 week - the programmable thermostat completes the period of Jolly and resumes the automatic mode. T1: The temperature set manually from 2 to 40°C.



OFF (turned OFF)

This mode is used to manage system operation for maintaining the antifreeze temperature, set from 2 to 7° C. Complete turn-OFF of the system Ta=OFF.

SPECIAL FUNCTIONS

These functions are selected accessing the technical menu of the programmable thermostat.

FREQUENT SETTINGS MENU

- Summer / Winter
- Summer time / Standard time
- Time / Day setting
- Lock function for screen cleaning.

CONFIGURATION MENU

- Celsius / Fahrenheit
- Temperature correction
- Time profile customization
- Backlight costumizable in intensity and duration
- 4 languages: Italian, English, French and Spanish
- Lock function with PIN code to prevent unauthorized setting changes.
- Default settings reset

FEATURES

Protection degree: IP20;

Acoustic signals: buzzer feedback with key pressing; Perpetual clock calendar, with backup battery;

Software Class A;

Minimum differential: ±0,1K; Thermal gradient: 4K/h;

Maximum ambient temperature: 45 °C.

ACCESSORIES

External probes

Weekly programmable thermostats series Intellitouch WiFi are designed for connecting external probes









EC18 external probe

EC19 floor probe

EC20 ambient probe

APP Intelliclima+

With the Intelliclima+ APP you're always connected to your Fantini Cosmi CH193WiFi programmable thermostat and you can manage your ideal comfort levels in a simple and intuitive way, from a smartphone or tablet, wherever you may be.

With Intelliclima+ you can:

- Switch the heating/cooling system on or off;
- Check the state of your system in real time;
- Choose your ideal temperature at any time and until when it set;
- Create your weekly or daily programme or choose from those preset;
- Optimise your comfort and save energy;
- Receive push notifications of generic alarms and anomalies in your system.

Use the Intelliclima+ APP for all your CH193WiFi programmable thermostats: at home or in the office, beach side or mountain side. Indeed, Intelliclima+ can control several homes and several programmable thermostats within a single home.







The features referring to the units described in this catalogue are not binding. Fantini Cosmi S.p.A. reserves the right to make modifications without prior notice, owing to technological advances, commercial and normative developments, notwithstanding to keep the main functional features of the described products.