

TECNOLOGY AND DESIGN FOR A SMART COMFORT



C900 SERIES

SMART WI-FI PROGRAMMABLE THERMOSTAT

FantiniCosmi

C900 SERIES

SMART WI-FI PROGRAMMABLE THERMOSTAT

Find out more



C900Q



C900QN



C900QS



C900R



C900RN



C900RS

- Sophisticated design:** high-quality materials and an elegant style line with three modern color options to suit any environment.
- Simplified usability:** three buttons to easily select various functions and ensure an optimal user experience.
- Versatile installation:** choose between a square or rectangular base and enjoy dual power options (batteries or 230V) to meet all your needs.
- Integrated smart functions:** thanks to the advanced smart features and built-in Wifi, save energy and optimize consumption with self-learning and dynamic geolocation.

TECHNICAL FEATURES

Temperature regulation range	2 ÷ 40 °C, increase 0,1°C
Power supply	2 batteries 1,5V AA or 230Vac @50Hz
Contacts rating	5[3]A 250 Vac
Adjustable differential	STD, 0,3 ÷ 5 K
Thermal gradient	4 K/h
Ambient RH display range	0 ÷ 99 %, increase 1%

HOMOLOGATION AND STANDARD

- Complies with EN 60730-1 standards; Compliant with Directive 2014/53 / UE (RED)
- Class IV; 2% (Reg. EU 811/2013 - 813/2013



INSTALLATION

- SQUARE BASE for wall mounting (battery-powered), or flush-mounting in a type 500 and 502 box (230V AC power supply).
- RECTANGULAR BASE for wall mounting (battery-powered), or flush-mounting in a type 503 box (230V AC power supply).
- C800AL power supply 230V AC/3.3V DC flush-mounting kit, compatible with C900 and C800 series



DYNAMIC GEOLOCATION



PERCEIVED TEMPERATURE



ENVIRONMENTAL SAVINGS



SELF LEARNING



DOUBLE POWER SUPPLY



OPEN WINDOW DETECTION



REMOTE CONTROL BY APP



INTEGRATED WIFI



RED DA
COMPLIANT

DIMENSIONS (mm)



FANTINI COSMI SPA
Via dell'Osio 6 - 20049 Caleppio di Settala MI, Italy
Ph. +39 02 95682.229 | Fax +39 02 95307006 | export@fantinicosci.com

www.fantinicosci.com